

ENDURO FACTORY 2 STROKE MY26

DATA SHEET	125 SE
Motor	Single-cylinder 2-stroke engine with Electronic control valve and booster
Displacement	124,81cc
Bore and stroke	54 x 54,50 mm
Fuel supply	Keihin PWK 36 carburetor
Cooling	Liquid cooling with forced circulation
Starting	Electric starter
Battery	BS Battery 12V 140A Lithium
Exhaust	Chromed exhaust pipe and aluminium silencer
Transmission	6-speed transmission – gear drive primary and chain drive secondary
Clutch	Hydraulic, multi-disc in oil bath
Ignition	220 W Alternator
Chassis	Semi-perimetric high-strength chrome-molybdenum steel
Fuel tank	10 L capacity
Brakes	Brembo hydraulic brakes, 260 mm Ø (front) - 220 mm Ø (rear)
Front suspension	Closed cartridge KYB fork with settings and spring rates specific to each model. 48 mm Ø fork legs - 300 mm stroke
Rear suspension	KYB 50 shock absorber with hydraulic settings and spring rates specific to each model 18 mm Ø - 330 mm stroke
Front wheel	1.60 x 21'' black anodized Excel rim, Michelin Enduro Medium tire
Rear wheel	2.15 x 18'' black anodized Excel rim, Michelin Enduro Medium tire
Wheelbase	1465 mm
Ground clearance	355 mm
Saddle height	950 mm

